

ETA / ETA LED / DD44LDRA14

## Product Info




<b>Item code</b>	ETA LED / DD44LDRA14
<b>Category</b>	Surface, Wall , Suspended
<b>Environments</b>	industrial areas, car park, plant rooms, warehouse
<b>Mounting type</b>	Surface / suspension
<b>Body</b>	Glass reinforced polyester (GRP) housing and Polymethylmethacrylate (PMMA) diffuser, V2A stainless steel clips
<b>Seals</b>	Polyurethane foam gasket.
<b>Wiring</b>	Electrical harness wired for 220-240V-AC 50-60Hz power supply. 2.5mm <sup>2</sup> LTN terminal block. DALI dimmable electronic ballast.
<b>Standard Colour</b>	Grey (RAL7035)



## Dimensions


<b>Total device width (mm)</b>	90
<b>Total device length (mm)</b>	1519
<b>Total device height (mm)</b>	105



## Optical System

<b>Diffuser</b>	PMMA
<b>Optical System</b>	Diffused
<b>Beam</b>	120°
<b>Emission</b>	direct
<b>Adjustable</b>	No

## Photometrics



## Sources

<b>MacAdam</b>	Step 3
<b>Output Flux</b>	6200 lm
<b>Source type</b>	LED
<b>System power</b>	43W
<b>Temperature Colour</b>	4000K CRI>90

## Electrical

<b>Ballast type</b>	DALI.
<b>Frequency</b>	50-60Hz
<b>Lifetime</b>	50.000h L70B20 (Ta=25°C)
<b>Line input</b>	Electrical harness wired for 220-240V AC/50-60Hz
<b>Mounting ballast type</b>	Integral
<b>Voltage</b>	220-240V
<b>Separate ignition</b>	No
<b>Emergency 1E</b>	No
<b>Emergency 3E</b>	No